## **MOUNTED TYPE TURBO ATOMIZER**





\*\*\*\*\*\*





## **GENERAL FEATURES**

It has polyester and polyethylene depot and membrane pumps, which are operated by power take-off from tractor conveys pressuring chemical liquid to nozzles on fan. Fan is also operated with power- take off and it sends pressured air out. Pressured chemical liquid is sprayed by adjustable nozzles around the fan by air circulation. Atomization is provided on right or left sides by remote control.

## **TECHNICAL DETAILS**

CODE	CAPACITY (LT)	MATERIAL OF DEPOT	TYPE OF MACHINE	DIAMATER OF FAN	NUMBER OF NOZZLE	PUMP	NUMBER OF DIAPHRAGM PISTON	FLOW RATE (LT/MIN.)	PRESSURE (BAR)	PTO ROTATION (RPM)
SMTA-200	200	PLASTIC	BELT-SEPARATOR	60 CM	8	S-80	3	80	50	540
SMTA-300	300	PLASTIC	BELT-SEPARATOR	60 CM	8	S-80	3	80	50	540
SMTA-400	400	PLASTIC	BELT-SEPARATOR	60 CM	8	S-80	3	80	50	540
SMTA-400	400	PLASTIC	BELT-SEPARATOR	75 CM	10	S-105	4	105	50	540
SMTA-500	500	PLASTIC	BELT-SEPARATOR	75 CM	10	S-105	4	105	50	540
SMTA-600	600	PLASTIC	BELT-SEPARATOR	75 CM	10	S-105	4	105	50	540
SMTA-600	600	PLASTIC	GEARBOX	75 CM	10	S-105	4	105	50	540
SMTA-800	800	PLASTIC	GEARBOX	75 CM	10	S-105	4	105	50	540



HEAD OFFICE

**FACTORY** 

Add: Fevzi Cakmak Mh. 10758 Sk. No: 16/G 42050 Karatay/Konya/TURKEY Add: Büyükkayacık Osb, Yaylacık Cd. No: 23, 42250 Selcuklu/Konya/TURKEY

T: +90 332 290 00 20 F: +90 332 290 00 19 T: +90 332 239 18 85 T: +90 332 239 18 86 F: +90 332 239 18 87

www.soilmaster.com.tr



+90 (532) 137 01 74



info@soilmaster.com.tr



